APPENDIX B RISK ASSESSMENT PROCEDURES FOR ORDNANCE AND EXPLOSIVES (OE) SITES

Site Name	Rater's Name
Site Location	Phone Number
DERP Project #	Organization
Date Completed	Score
<u> </u>	,

OE RISK ASSESSMENT:

This risk assessment procedure was developed in accordance with MIL-STD 882C and AR 385-10. The Risk Assessment Code (RAC) score will be used by the U.S. Army Engineering and Support Center, Huntsville (USAESCH), Ordnance and Explosives Team (USAESCH-OE) to prioritize the response action(s) at Formerly Used Defense Sites (FUDS). The risk assessment should be based on the best available information resulting from record searches, reports of Explosive Ordnance Disposal (EOD) Detachments actions, field observations, interviews, and measurements. This information is used to assess the risk involved based on the <u>potential</u> OE hazards identified at the site. The risk assessment is composed of two factors, <u>hazard severity</u> and <u>hazard probability</u>. Personnel involved in visits to potential OE sites should view the USAESCH-OE videotape entitled "A Life Threatening Encounter: OEW".

Part I. <u>Hazard Severity</u>. Hazard severity categories are defined to provide a qualitative measure of the worst credible event resulting from personnel exposure to various types and quantities of unexploded ordnance.

TYPE OF ORDNANCE: (Circle all that apply)		
A. Conventional ordnance and ammunition:		
Medium/large caliber (20mm and larger)	10	
Bombs, explosive	10	
Grenades, hand or rifle, explosive	10	
Landmine, explosive	10	
Rockets, guided missile, explosive	10	
Detonators, blasting caps, fuzes, boosters, bursters	6	
Bombs, practice (w/spotting charges)	6	
Grenades, practice (w/spotting charges)	4	
Landmine, practice (w/spotting charges)	4	
Small arms, complete round (.22 cal50 cal)	1	
Small arms, expended	0	
Practice ordnance (w/o spotting charges)	0	
Conventional ordnance and ammunition (largest single value)		

nance?
VALUE
10
6
4
VALUE
10
10
8
6
3

ordr	nance; uncontainerized):	
		VALUE
	Solid or liquid propellants	(
	Propellants	
Wł	nat evidence do you have regarding bulk propellants?	
 E.	Chemical Warfare Materiel (CWM) and Radiological	VALUE
	apons:	VILLEI
	Toxic chemical agents (choking, nerve, blood, blister)	25
	War Gas Identification Sets	20
	Radiological	15
	Riot Control Agents (vomiting, tear)	5
Che	emical and Radiological (select the single largest value)	
Wha	at evidence do you have regarding chemical or radiological?	
TO	ΓAL HAZARD SEVERITY VALUE (Sum of value A through E (maximum 1)	

Bulk propellants (not an integral part of rockets, guided missiles, or other conventional

D.

Apply this value to Table 1 to determine Hazard Severity Category

TABLE 1 HAZARD SEVERITY*

DESCRIPTION	CATEGORY	HAZARD SEVERITY VALUE
CATASTROPHIC CRITICAL MARGINAL NEGLIGIBLE **NONE	I II III IV V	21 and/or greater 10 to 20 5 to 9 1 to 4

^{*}Apply Hazard Severity Category to Table 3

PART II. <u>Hazard Probability</u>. The probability that a hazard has been, or will be, created due to the presence and other rated factors of unexploded ordnance or explosive materials on a formerly used Department of Defense (DOD) site.

AREA, EXTENT, ACCESSIBILITY OF OE HAZARD (Circle all that apply)

A.	Locations of OE hazards:	VALUE	
	On the surface	5	
	Within tanks, pipes, vessels, or other confined areas	4	
	Inside walls, ceilings, or other building/structure	3	
	Subsurface	2	
Location (select the single largest value)			
What	evidence do you have regarding the location of OE?		

^{**}If hazard severity value is 0, you do not need to complete Part II of this form. Proceed to Part III and use a RAC score of 5 to determine your appropriate action.

B. likel	Distance to nearest inhabited location/structure y to be at risk from OE hazard (road, park,	VALUE
	ground, building, etc.)	
	Less than 1,250 feet	5
	1,250 feet to 0.5 mile	4
	0.5 mile to 1.0 mile	3
	1.0 mile to 2.0 Miles	2
	Over 2 miles	1
Dist	ance (select the single largest value)	
Wha	at are the nearest inhabited structures/buildings?	
C.	Number(s) of building(s) within a 2-mile radius	VALUE
mea	sured from the OE hazard area, not the installation	
bour	ndary.	
	26 and over	5
	16 to 25	4
	11 to 15	3
	6 to 10	2
	1 to 5	1
	0	0
Nun	nber of buildings (select the single largest value)	
Narı	rative:	
D.	Types of Buildings (within a 2 mile radius)	VALUE
	Educational, child care, residential, hospitals	5
	hotels, commercial, shopping centers	
	Industrial, warehouse, etc.	4

EP 1110-1-18 24 Apr 00

Agricultural, forestry, etc.	3	
Detention, correctional	2	
No buildings	0	
Types of buildings (select the single largest value)		
Describe the types of buildings:		
E. Accessibility to site refers to access by humans to ordnance and explosives. Use the following guidance:	VALUE	
No barrier nor security system	5	
Barrier is incomplete (e.g., in disrepair or does not completely surround the site). Barrier is intended to deny egress from the site, as for a barbed wire fence for grazing.	4	
A barrier (any kind of fence in good repair) but no separate means to control entry. Barrier is intended to deny access to the site.	3	
Security Guard, but no barrier	2	
Isolated site	1	
A 24-hour surveillance system (e.g., television monitoring or surveillance by guards or facility personnel continuously monitors and controls entry; or, an artificial or natural barrier (e.g., fence combined with a cliff) which completely surrounds the area; and, a means to control entry at all times through the gates or other entrances (e.g., an attendant, television monitors, locked entrances, or controlled roadway access to the area).	0	
Accessibility (select the single largest value)		

Describe the site accessibility:	
F. Site Dynamics. This deals with site conditions are subject to change in the future, but may be stable at the present. Examples would be excessive soil erosion on beaches or streams, increasing land development that could reduce distances from the site to inhabited areas or otherwise increase accessibility.	VALUE
Expected None anticipated	5 0
Site Dynamics (select the single largest value)	
Describe the site dynamics;	
TOTAL HAZARD PROBABILITY VALUE (sum of largest values for A of 30)	through F (maximum

Apply this value to Hazard Probability Table 2 to determine the Hazard Probability Level.

TABLE 2 HAZARD PROBABILITY

DESCRIPTION VALUE	<u>LEVEL</u>	HAZARD PROBABILITY
FREQUENT	A	27 or greater
DD OD A DI E	D	
PROBABLE	В	21 to 26
OCCASIONAL	C	15 to 20
OCC/IDIOIVIE	C	13 to 20
REMOTE	D	8 to 14
H (DDOD A DI E	T	1 1 0
IMPROBABLE	E	less than 8

^{*}Apply Hazard Probability Level to Table 3.

EP 1110-1-18 24 Apr 00

Part III. Risk Assessment. The risk assessment value for this site is determined using the following Table. Enter the results of the Hazard Probability and Hazard Severity values.

TABLE 3

PROBABILITY LEVEL	FREQUENT A	PROBABLE B	OCCASIONAL C	REMOTE D	IMPROBABLE E
SEVERITY CATEGORY:					
CATASTROPHIC I	1	1	2	3	4
CRITICAL II	1	2	3	4	5
MARGINABLE III	2	3	4	4	5
NEGLIGIBLE IV	3	4	4	5	5

RISK ASSESSMENT CODE (RAC)

- RAC 1 Expedite INPR, recommending further action by USAESCH-Immediately call USAESCH-OE-S (comm 256-895-1582/1598).
- RAC 2 High priority on completion of INPR-Recommend further action by USAESCH.
- RAC 3 Complete INPR-Recommend further action by USAESCH.
- RAC 4 Complete INPR-Recommend further action by USAESCH.
- RAC 5 Usually indicates that No DOD Action Indicated (NDAI) is necessary, Submit NDAI and RAC to USAESCH.

PART IV. Narrative. Summarize the documented evidence that supports this risk assessment. If no documented evidence was available, explain all the assumptions that you made.